



Electricity is now intelligent.

- LED STREET LIGHTS
- LED DOWNLIGHTERS
- LED LAMPS
- LED FLOOD LIGHTS
- LED WALL WASHERS
- LED STRIP LIGHTS
- LED TRACK LIGHTS





Incandescent | E26 Medium & E12 Candelabra Base

This is the traditional "Edison" light bulb. It emits light in a warm, broad spectrum; however, approximately 90% of all the power consumed by an incandescent light bulb is emitted as heat rather than visible light. Given far more efficient alternatives, some governments are mandating a phase-out or ban of its use.



Halogen | T3 Bi-Pin, G4 Base & MR16, GU5.3 Base

Halogen is a form of incandescent. It has the truest color rendering of any light source other than the sun and is therefore often used to illuminate works of art. In the MR16 format, this long-lasting, low-voltage spot is amplified by an integrated reflector, greatly increasing its apparent efficacy.



Ceramic Metal Halide | E26 Medium Base

Metal Halide is an efficient, high-output lamp commonly used to illuminate large outdoor areas, in part because its output is unaffected by environmental temperature changes. Due to high intensity and slow start-up, it is best suited for outdoor and commercial applications. MHs contain mercury, requiring special disposal measures.



Light-Emitting Diodes (LEDs)

LEDs are a promising technology currently undergoing rapid development. Their warmth and color rendering can be comparable to incandescent in certain applications. Their small size makes them highly versatile. Given their long life, high efficiency and low toxicity, their cost is likely to be justified over time.



Compact Fluorescent (CFL) | Integrated Ballast | GU-24 Pin & E26 Medium Base

CFLs use less energy than incandescents and can last up to eight times longer (if not overheated) while generating light that is becoming increasingly comparable. CFLs contain trace amounts of mercury, requiring special disposal measures. The ballast must be discarded along with this type of lamp.



CFL non-integrated ballast | Twin & Quad Tube | 2G11 & GX24Q, 2 & 4 Pin Base

These CFLs utilize separate, reusable electronic ballasts; they are slightly more efficient and can last longer compared to integrated-ballast CFLs. One ballast will often run multiple wattages and permit dimming. Lamp disposal issues are the same.



High Pressure Sodium (HPS) & White "SON"

These lamps are typically used for streetlights and security lighting, where color rendering is not critical. HPS lamps contain trace amounts of mercury, making disposability an issue, and they decline in lumen output as they age. White "SON" is a higher cost HPS variant with a high CRI but reduced life and efficacy.



Fluorescent Tube | T5, T5 HO Mini Bi-Pin, T8

The "new and improved" flicker-free fluorescent tube offers good color rendering, long life and low cost. Like all fluorescents, special disposal measures are required due to mercury content.

White Placard

LAMPING COMPARISON CHART

www.whiteplacard.com

ENERGY watts	OUTPUT lumens	EFFICACY lumens per watt	CO2 lbs	CO2: lumen ratio	LAMP COST	LIFE (hours)	RUN COST per 1000 hrs	CRI 1-100	CCT kelvin
25	170	07	33	.194			\$3.60		
40	495	12	46	.105	\$0.60	1000	\$5.40	100	2700
60	830	14	78	.093			\$7.80		
<hr/>									
BI-PIN 20						2K to 4K	\$3.40	100	2850
20	320	16	26	.081	\$2.00		\$3.06		
MR16 35						2K to 4K	\$5.80	100	2950 to 6000
35	600	17	46	.077	\$5.00		\$9.26		
50	900	18	65	.072	\$0.79				
<hr/>									
22	1155	53	27	.023	\$88		\$0.94		
70	4500	64	91	.020	\$32	12K	\$11.06	81-96	2900 to 4100+
150	9800	65	195	.020	\$31		\$20.50		
<hr/>									
02	200	100*	03	.015	\$20		\$0.71		
05	500	100*	07	.014	\$38	35K to 50K	\$1.49	40-90	2900 to 6100
10	1000	100*	13	.013	\$80		\$3.06		
<hr/>									
13	850	65	17	.020	\$3.20		\$1.88		
18	1100	61	23	.020	\$4.40	10K	\$2.60	82-90	2700 to 4100
23	1600	69	30	.018	\$4.00		\$3.16		
<hr/>									
26	1800	69	34	.019	\$7.40		\$3.58		
32	2400	75	42	.018	\$10.00	12K to 20K	\$4.47	82-90	2700 to 6500
36	2800	78	47	.016	\$10.60		\$4.98		
80	6000	75	104	.017	\$28.00		\$11.35		
<hr/>									
HPS 35						16K	\$5.68		
35	2250	64	46	.020	\$23.70	24K	\$9.38	22	1900
70	6400	91	91	.014					
SON 50						10K	\$13.95	85	2500 to 2700
50	2000	40	65	.032	\$79.50		\$19.95		
100	4170	42	130	.031					
T5 28						25K to 35K	\$3.68	82-85	3000 to 6500+
28	2900	104	31	.015	\$9.74		\$4.52		
35	3450	99	70	.014					
T8 17						20K to 46K	\$2.18		3000 to 6500
17	1260	80	22	.017	\$4.84		\$3.91	78-96	
32	2800	80	46	.016	\$2.54				

1 Lumens are a measurement of the perceived power of light. All ratings approximate. 2 efficacy = lumens/watts. The higher the number, the more efficient.
 3 Approximate CO2 emission per 1,000 hours of use assuming coal generated electricity. 4 CO2 output per lumen is a finer gauge of sustainability.
 5 Costs are collected averages. 6 Includes electricity at national average of 12c/kwh, and average lamp cost. 7 CRI = Color Rendering Index. 100 = full color range; incandescent. 8 CCT = Correlated Color Temperature in degrees Kelvin. Low temps are "warm" colors, high "cool".* Actual efficacies measured in application are generally between 40-60. This is rapidly improving.

DISCLAIMER

WHITE PLACARD TECHNOLOGIES RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS OR INFORMATION HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. WHITE PLACARD TECHNOLOGIES IS NOT RESPONSIBLE FOR ANY INFORMATION CONTAINED IN THIS DOCUMENT TO BE VARYING FROM THE ACTUAL DATA. WHITE PLACARD TECHNOLOGIES DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

WHITE PLACARD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF WHITE PLACARD TECHNOLOGIES. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

For more information regarding our products and services, please log onto www.whiteplacard.com